


NOTES:
1. SUGGESTED MOUNTING HOLE = ϕ .130


LEAD FINISH: GOLD PL.	
CASING FINISH: GOLD PL.	
CAPACITANCE	1000pF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C -- VAC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	--
10	8
100	25
1 GHz	40
10 GHz	42

SCHEMATIC



MARKING:

PART: WHITE COLOR DOT
BAG:
SCI-9980-102
DATE CODE
LOT NO.
QTY/BAG (200 MAX.)

CN 53139-ENG	00	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 FAIRVIEW PENNSYLVANIA SPECTRUM CONTROL INC.		
	CHANGE NOTICE	Fractions ± 1/64	Dwn. KAUFFMAN		Description	
		Dec. .xx ±	Dec. .xxx ± .005		Date 3-01-10	FEEDTHRU FILTER
		Angles ± 0° 30'	CODE IDENT. NO. DLSP2		Engr. B. DEVINE	SCI-9980-102
					Scale NONE	