

**RIDERSERIES
RCL334024**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Standard relays in the RIDERSERIES RCL

- 1 NO contact
- Low height of 15.7 mm

General ordering data

Order No.	8693280000
Type	RCL334024
Version	RIDERSERIES, Relais, No. of contacts: 1, NO contact, AgNi 90/10, Rated control voltage: 24 V DC, Continuous current: 16 A, Plug-in connection
GTIN (EAN)	4032248364732
Qty.	20 pc(s).

RIDERSERIES
RCL334024

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Ratings

Conductor connection system	Plug-in connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Weight	14 g	UL 94 flammability rating	V-0

Dimensions and weights

Width	12.7 mm	Height	29 mm
Depth	15.7 mm	Weight	14 g
Net weight	15 g		

Temperatures

Operating temperature	-40 °C...+70 °C	Storage temperature	-40 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

Input

Rated control voltage	24 V DC	Rated current DC	16.7 mA
Coil resistance	1,440 Ω ±10 %	Power rating	500 mW
Pull-in (sparkover) / drop-out voltage DC coil	16.8 V / 2.4 V		

Output

Rated switching voltage	250 V AC	Max. switching voltage, AC	400 V
Continuous current	16 A	making current	30 A / 4 s
Max. switching power	4000 VA	Switch-on delay	≤ 8 ms
Switch-off delay	≤ 6 ms	Min. switching power	100 mA / 5 V, 10 V / 10 mA, 24 V / 1 mA
Max. switching frequency at rated load	0.1 Hz		

Contact specifications

No. of contacts	1	Contact design	NO contact
Contact material	AgNi 90/10	Mechanical service life	AC coil 10 x 10 ⁶ Switching cycles, DC coil 30 x 10 ⁶ Switching cycles

Insulation coordination

Rated voltage	250 V	Clearance and creepage distances for control side - load side	≥ 10 mm
Dielectric strength for control side - load side	5 kV _{eff} / 1min	Protection degree	IP 20
Insulating material group	IIIa		

Other technical data

Version	Relay	Free-wheel diode	No
---------	-------	------------------	----

Further details of approvals / standards

Standards	IEC 61810-1, UL508
-----------	--------------------

**RIDERSERIES
RCL334024**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
UNSPSC	30-21-19-17	eClass 4.1	40-02-06-14
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01
eClass 7.0	27-37-16-01		

Approvals

Approvals



**RIDERSERIES
RCL334024**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)

Base



Relay base for RIDERSERIES RCL relays

- Screw and tension clamp connection
- Standard and low heights
- Plug-in frame for PCB connections

General ordering data

Order No.	Type	Version	GTIN (EAN)	Qty.
8693930000	SRC 2CO N	RIDERSERIES, Relay base, Screw connection	4032248365418	10 pc(s).
8783930000	SRC 2CO Z	RIDERSERIES, Relay base, Tension clamp connection	4032248471430	10 pc(s).
8690830000	SRC 2CO	RIDERSERIES, Relay base, Screw connection	4032248361519	10 pc(s).

Base



Relay base for the RIDERSERIES RCI relays

- 1 and 2 CO contacts
- Screw and PUSH IN connection
- Standard and low heights

General ordering data

Order No.	Type	Version	GTIN (EAN)	Qty.
8869500000	SRC-I 2CO P	RIDERSERIES, Relay base, Continuous current: 16 A ⁽¹⁾ , 8 A, PUSH IN spring connection	4032248614455	10 pc(s).