


IC0805C470R-10

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS:

- A 2.00 [.079] \pm 0.20 [.008]
- B 1.25 [.049] \pm 0.20 [.008]
- C 0.85 [.033] \pm 0.20 [.008]
- D 0.50 [.020] \pm 0.30 [.012]



NOTES: UNLESS OTHERWISE SPECIFIED


1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 7" REELS, 4000 PCS/REEL, EMBOSSED PLASTIC TAPE.
2. TERMINATION FINISH IS 100% MATTE Sn OVER Ni.
3. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
4. I (MAX.) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MAXIMUM TEMPERATURE RISE OF 40°C OVER AMBIENT.
5. I (OPERATING) IS BASED ON THE MAXIMUM SUSTAINED CURRENT APPLIED WHILE MAINTAINING A MINIMUM INDUCTANCE (L).
6. OPERATING TEMP. RANGE: -40°C~+125°C. (INCLUDING SELF-HEATING)

ELECTRICAL CHARACTERISTICS:




L (nH) \pm 10%	52	Max
	47	Nom
	42	Min@ 300mA
Q (Min)	15	
Freq. (MHz)	50	
Self-Resonant Freq (MHz)	320	
DCR(Max) Ω	0.20	
I (Max)	300mA	
I (Operating)	300mA	

LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 [.030] to this dimension)

RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
C ADD OPERATING TEMPERATURE UPDATE LAIRD LOGO AND REFLOW CURVE 08/05/13 QU				PROJECT/PART NUMBER: IC0805C470R-10			
B UPDATE COMPANY LOGO 06/24/08 JRK				DATE: 01/02/07			
A ORIGINAL DRAFT 01/02/07 JRK				SCALE: NTS			
REV DESCRIPTION DATE INT				TOOL # -			
				SHEET: 2 of 2			

