




- NOTES:
 1. SUGGESTED MOUNTING HOLE = ϕ .218 [5.54]
 2. HARDWARE IS INCLUDED.

LEAD FINISH: SILVER	
BUSHING FINISH: SILVER	
CAPACITANCE	1 μ F +80/-20%
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	85°C 80VDC MAX. 125°C 50VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
30 KHz	10
50 KHz	15
100KHz	20
1	40
10	52
100	70
500	78
1 GHz	80
SCHEMATIC 	
MARKING: PART: SCI 105Z	
BAG: 54-786-014 DATE CODE QTY./BAG (50 MAX.)	
	

	48	47	46	45	44	43	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED
	CN #14633	CN 56108-ENG	CN 31263-CPD	CN 19975-CPD	CN. 19494-CPD	CN. 184932	CHANGE NOTICE	Fractions $\pm 1/64$
								Dec. .xx \pm
								Dec. .xxx \pm 015 [.38]
								Angles $\pm 0^{\circ} 30'$
								CODE IDENT. NO. 0LSP2

api  **FAIRVIEW PENNSYLVANIA**
 technologies corp.

Dwn.KAUFFMAN	Description FEED THRU RESIN SEAL FILTER
DATE 7-17-15	
ENGR. M.McALEVY	54-786-014
DO NOT SCALE	