

**KEMET Part Number: MMK5104K63J01L4BULK**  
(F601JF104K063C)



Film, Metallized Polyester, Commercial Grade, MMK/F601, 0.1 uF, 10%, 63 V, 85C, Lead Spacing = 5mm



General Information	
<b>Dielectric:</b>	Metallized Polyester
<b>Style:</b>	Radial
<b>Series:</b>	MMK/F601
<b>Features:</b>	Pulse
<b>RoHS:</b>	Yes
<b>Lead:</b>	Wire Leads
<b>Miscellaneous:</b>	Not For New Design, Please Check Possible Alternative Parts (AltPart)

Dimensions	
<b>L</b>	7.2mm MAX
<b>H</b>	6.5mm MAX
<b>T</b>	2.5mm MAX
<b>S</b>	5mm +/-0.4mm
<b>LL</b>	5mm NOM
<b>F</b>	0.5mm NOM

Specifications	
<b>Capacitance:</b>	0.1 uF
<b>Capacitance Tolerance:</b>	10%
<b>Voltage DC:</b>	63 VDC, 48.8 VDC (100C)
<b>Voltage AC:</b>	40 VAC
<b>Temperature Range:</b>	-55/+100C
<b>Rated Temperature:</b>	85C
<b>Dissipation Factor:</b>	0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz
<b>Insulation Resistance:</b>	15 GOhms
<b>Max dVdt:</b>	25 V
<b>Inductance:</b>	6 nH

Packaging Specifications	
<b>Packaging:</b>	Bulk
<b>Packaging Quantity:</b>	2000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2017 IntelliData.net